

VisBlue vanadium redox flow battery – outdoor module

Power and capacity				
Energy storage capacity [kWh]	Scalable up to 50			
Nominal charge/discharge power [kW]	Scalable up to 20	In steps of 2.5 kW		
For larger systems multiple modules can be assembled				
Peak charge/discharge power	1.5 x nominal power	30 min. on / 30 min. off		
DC efficiency (stack)	80%	DC roundtrip include both charge and discharge efficiency		
AC efficiency (system) @ nominal power	70%	AC roundtrip include both charge and discharge efficiency		
DC voltage	40V to 60V			
AC voltage	1x230VAC	3x400VAC 50Hz		
Grid connection	1 phase	3 phases		
Depth of charge and discharge	5% to 95%			
Response time	<20ms			
Self-discharge	<0.3% of full capacity per day with pumps stopped	<100 Wh per day for a 33 kWh system		
Remote access				
Communication	Remote access through LAN	Modbus TCP Receive address list on request		
Battery control	Charge/discharge is controlled by input from energy meter	Charge/discharge is controlled by input from external master		
Remote monitoring				
Cloud access	Data accessing from cloud			
Web page	Visualisation of front end data	Visualisation of back end data		
Size and mass				
Module size [tank in l]	600	800	1000	1250
kW/kWh	5/25	5/30	5/40	5/50
Footprint [mm] (WxD)	1710 x 2200	1710 x 2200	1710 x 2600	1710 x 2600
Height [mm]	2270	2270	2270	2270
Weight [kg]	2300	2800	3300	3800
Cycle and design life	20,000 cycles (20 years)			
Environment				
Ambient temperature [°C]	-10 to +40			
Humidity	95% RH non- condensing			
Ventilation	Depends on environment	Cooling/heating can be installed		
Safety	Non-flammable and non-explosive		Water based electrolyte	

Visit our website at: www.visblue.com

Enquiries: sales@visblue.com

